https://hi-IN.optomaeurope.com







- Bright SVGA projector 4000 lumens
- · Powerful audio with built-in 10W speaker
- ECO+ mode for extended lamp life up to 15,000 hours
- 25,000:1 high contrast

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the SA520 boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB power. Perfect for connecting HDMI dongles or a laptop, PC or Blu-ray player for clear projected images with sound. This portable and lightweight projector can be installed or taken on the move for off-site meetings.

Specifications

-	
Display/image	
Display technology	
Resolution	SVGA (800x600)
Brightness	4,000 lumens
Contrast ratio	25,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
/ertical scan rate	50 ~ 85(120 for 3D)Hz
Jniformity	75%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal
.amp info	Larra
ight source type	Lamp
_amp watts	203 6000 (Bright) 12000 (Duramia) 10000 (Eac) 16000 (Eacu)
amp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1.94:1 ~ 2.16:1
Projection distance	1m - 12m
loom loom turo	1.1 Monuel
Zoom type	Manual 21.85 mm~24mm
Focal length	
lative offset	115%
Connectivity Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x Composite
	video, 1 x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1A
General	
loise level (typical)	27dB
loise level (max)	29dB
PC compatibility	WUXGA,1080P,UXGA, SXGA+,SXGA ,WXGA+,WXGA,720P,XGA,SVGA,VGA
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Speaker count	1
Vatts per speaker	10W
n the box	AC power cord Remote control
	Basic user manual
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	187W
	225W
Power consumption (max)	
Power consumption (max) Weight and dimensions	
Weight and dimensions	320 x 240 x 98
, , ,	320 x 240 x 98 3.56 kg



Copyright © 2022, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 1012202045747